

Professional Loudspeaker

SE SERIES



SE-8



SE-10



SE-12



SE-15

FEATURES

- ❖ Trapezoidal two way speaker system
- ❖ HF driver Protection circuitry
- ❖ Titanium Compression Drivers
- ❖ Pole mount socket and 9 Rigging points for suspension(M8)
- ❖ Optimized enclosure design for smooth and extended response
- ❖ High quality rigid MDF board enclosure
- ❖ The advanced crossover design provides smooth and clear response
- ❖ Heavy duty grille

SPECIFICATIONS

MODEL	SE-8	SE-10	SE-12	SE-15
TYPE	Ultra-compact, two-way passive	Compact, two-way passive	Compact, two-way passive	Compact, two-way passive
FREQUENCY RESPONSE	65Hz~18kHz	55Hz~18kHz	40Hz~18kHz	38Hz~18kHz
DRIVERS	8" LF driver, 1" exit HF compression driver	10" LF driver, 1" exit HF compression driver	12" LF driver, 1" exit HF compression driver	15" LF driver, 1" exit HF compression driver
RATED POWER	100W AES, 400W peak	150W AES, 600W peak	250W AES, 1000W peak	300W AES, 1200W peak
SENSITIVITY	93dB(1w/1m)	94dB(1w/1m)	96dB(1w/1m)	97dB(1w/1m)
MAXIMUM SPL	112dB(1m)	114dB(1m)	117dB(1m)	119dB(1m)
NOMINAL IMPEDANCE	8ohms	8ohms	8ohms	8ohms
CROSSOVER FREQUENCY	2500Hz	2300Hz	2150Hz	2000Hz
DISPERSION(-6dB)	75° horizontal, 60° vertical	75° horizontal, 60° vertical	75° horizontal, 60° vertical	75° horizontal, 60° vertical
CONNECTORS	2×NL4	2×NL4	2×NL4	2×NL4
FITTINGS	3×M8, 1×mounting pole socket	6×M8, 1×mounting pole socket	6×M8, 1×mounting pole socket	6×M8, 1×mounting pole socket
DIMENSIONS	296(W)×290(D)×460(H)mm 12(W)×12(D)×18.4(H)in	362(W)×355(D)×545(H)mm 14.5(W)×14.2(D)×22(H)in	422(W)×415(D)×665(H)mm 18(W)×17(D)×27(H)in	480(W)×470(D)×736(H)mm 19.2(W)×19(D)×29.4(H)in
WEIGHT	13kg / 28.66lb	17.4kg / 38.36lb	22.8kg / 50.26lb	32kg / 70.55lb

Inter-M Corporation

- OFFICE: 653-5 BANGHAK-DONG, DOBONG-KU, SEOUL, KOREA
- TEL: 82-2-2289-8140-8, FAX: 82-2-2289-8149

- Home page: <http://www.inter-m.com>
- E-mail: overseas@inter-m.com
- Printed in china

www.inter-m.com
2009.06

PROFESSIONAL LOUDSPEAKER